



PRODUCT DATA

CORROSION MANAGEMENT SOLUTIONS

ARMOR POLY® VCI FILM THE SENTINEL™

FEATURES AND BENEFITS

Metallized PET is a versatile material with applications that extend beyond the food industry. While commonly used to keep items fresh on store shelves (e.g., potato chips, toaster pastries, and granola bars), ARMOR has combined it with ARMOR POLY® VCI Film to create **ARMOR SENTINEL™ VCI Film**—a premium rust-prevention product.

ARMOR SENTINEL VCI Film utilizes the durability and strength of metallized PET to provide a physical barrier against oxygen, moisture and other contaminants. At the same time, ARMOR VCI (vapor corrosion inhibitor) Nanotechnology™ forms a clean, safe, easy-to-use molecular barrier to prevent rust. By laminating metallized PET onto the poly film, ARMOR has engineered a rugged, resilient VCI film with superior corrosion inhibition and barrier properties.

SENTINEL VCI Film is ideal for export shipments and for protecting metal parts and equipment from corrosion during long-term storage. It is non-hazardous, environmentally friendly and recyclable.

PRODUCT OVERVIEW

All Armor Protective Packaging® products utilize our proprietary and time-proven ARMOR VCI (vapor corrosion inhibitor) Nanotechnology™. Oxidation occurs when an electrolyte (water, oxygen, etc.) is present on the surface of a metal. The corrosion process begins when electrons flow through the electrolyte from high energy areas (anode) to low energy areas (cathode) of the metal. ARMOR VCI blocks this reaction by passivating the surface and inhibiting the electrochemical current flow from anode to cathode. ARMOR VCI's protective vapors adhere to a metal surface to form an invisible film only a few molecules thick to protect metal from attack.

ABOUT ARMOR

Armor Protective Packaging® offers rust prevention and rust removal products that are clean, safe, easy, and that protect metals while in-process, in transport, or in storage. ARMOR combines its VCI (vapor corrosion inhibitor) Nanotechnology™ with packaging materials such as paper and poly film to create products that displace moisture on metal and guard against rust. ARMOR also offers desiccants, emitters, foam pads and its Metal Rescue® Rust Remover Bath and Dry Coat™ Rust Preventative. For more than 45 years, ARMOR has worked with customers from around the globe to provide rust prevention and rust removal solutions and to Take the Work Out of Your Workday!



You won't find a customer service team on this earth more excited to talk about rust, so give our corrosion needs a call with your questions and make their day.

800.365.1117



ARMOR SENTINEL™ VCI FILM

ARMOR SENTINEL™ VCI Film utilizes advanced polyethylene film extrusion and lamination to combine three engineered layers to provide outstanding barrier properties and corrosion resistance.

Outside Layer (BoPET - Biaxially oriented Polyethylene Terephthalate): Provides strength, clarity and exceptional barrier properties. Its unique manufacturing process ensures consistent performance and durability, while maintaining a high-quality, lightweight nature that minimizes environmental impact.

Center Layer (Aluminum Deposit): Contains a thin layer of aluminum that enhances the film's barrier properties against moisture, oxygen, and light and improves the film's performance, extending product shelf life. The metallized surface also imparts an attractive and reflective appearance.

Inside Layer (ARMOR POLY® VCI): A low-density polyethylene blend with high concentration of multi-metal VCI and a specialty catalyzed polymerization resin. It releases rust-preventing vapors that form a protective molecular barrier on the surface of metal to prevent corrosion.

CONFORMS TO:

- FDA use in equipment packaging
- Global OEM companies
- RoHS – REACH Compliant
- NACE Std TM0208-2008

Compatibility of ARMOR POLY with Metals

Metal to be Protected	ARMOR POLY® Films
Aluminum	★ ★ ★
Aluminum Bronze	★ ★
Aluminum Magnesium alloy	○
Brass	★ ★ ★
Bronze	★ ★
Cadmium	★ ★
Cast Iron	★ ★ ★
Chromium	★ ★
Constantan	★ ★
Copper	★ ★ ★
Galvanized	★ ★ ★
Lead	○
Molybdenum	○
Nickel	★ ★ ★
Nickel Silver (CU, Ni, Zn)	★ ★ ★
Silver	★
Solder (Pb, Sn)	○
Steel	★ ★ ★
Tin (Pure)	★ ★ ★
Tinned Steel	★ ★ ★
Zinc	○

Compatibility Key

★ ★ ★ Complete Protection

★ ★ Good Protection

★ This product will protect this metal from corrosion; however, a more suitable formula may be available.

○ Testing is recommended

SHELF LIFE & STORAGE OF ARMOR VCI PRODUCTS

ARMOR POLY® VCI Film in individual sheets or bags has a shelf life of two years from the date of manufacture when stored in original packaging. ARMOR POLY rolled goods have a longer shelf life of three years from the date of manufacture when stored in original packaging.

For best results, do not leave ARMOR VCI packaging out in an open environment, either indoors or outdoors. Keeping it in its original packaging or enclosed inside a container ensures that the vapors remain in the packaging. As temperature and humidity levels increase, the rate of the volatilization of the chemicals contained in the packaging also increases, reducing the effectiveness and longevity of the product. Product should be stored in a dry environment with temperatures between 40° – 110° F (5° – 43°C).

Note: *While Shelf Life and Length of Protection are two separate characteristics of VCI packaging materials, they are somewhat interrelated. Shelf Life refers to how long the unused VCI packaging material can be stored prior to being put in use. Length of Protection refers to how long the VCI packaging materials provide protection once in use. In both cases the duration depends on the product's storage conditions.*

REUSABILITY

ARMOR POLY® VCI Film is not recommended for re-use for three primary reasons:

1. The rate at which VCI chemical volatilizes out of the product into the surrounding environment when in use
2. The inability to properly track and monitor the amount of time the materials have been exposed to the environment
3. Potential contaminants on the packaging that can be transferred

For those instances when re-use is necessary, be sure the packaging is free of dirt, holes, or other contaminants. Once these factors appear, it is best to use new, clean ARMOR VCI packaging. It is also important to note that the length of time the packaging material has been exposed to the environment (especially high heat/humidity) will greatly impact the effectiveness of the product. Do not re-use VCI packaging more than two times. Please note, ARMOR cannot guarantee the amount of VCI that remains in the packaging upon re-use.

LENGTH OF PROTECTION & LONG-TERM STORAGE

ARMOR VCI products are used to cover or wrap metal parts and surfaces. The continuous vaporization of this chemically treated packaging creates a safe, protective environment that effectively blocks out rust, corrosion, and oxidation. **ARMOR SENTINEL™ VCI Film** will protect parts for approximately 10-15 years when used properly in normal warehouse conditions. However, by following the guidelines below, it is possible to lengthen this time-frame considerably. The key element in protecting parts for long-term storage is ensuring that the metal part is completely clean, prior to wrapping in ARMOR products. We recommend that parts be completely wrapped or enclosed in airtight packaging for best results and longest protection time.

ARMOR cannot control variable conditions such as temperature and humidity extremes, airflow, production and process methods, surface conditions of metal to be protected, customer employee training and other factors beyond our control, therefore it is impossible to guarantee a specific length of protection. Additionally, if warehouse conditions are expected to be severe (i.e., over 90° F and 75% RH) for any length of time, other methods of rust preventatives such as Dry Coat™ RP or desiccants, may be needed, in conjunction with VCI packaging. Successful long-term storage requires that all of these guidelines be met. It is important to test parts and packaging as extensively as possible, prior to conducting any long-term storage projects.

GUIDELINES FOR SUCCESSFUL LONG-TERM STORAGE

- It is necessary to wear gloves when coming in contact with metal, as fingerprints (which contain human oils and possibly contaminants) can cause a chemical reaction to the metal prior to wrapping in ARMOR packaging. Make sure that gloves are clean and as they become dirty or contaminated, be sure to replace them with a new supply.
- Be sure your product is free of fingerprints, machining oils and acid or alkali residue. Neutral oils or a light rust inhibitor may be left on metal surfaces but may require laboratory testing to make sure there is compatibility between the VCI Packaging and the oils. Make sure that coolants, RP liquids and or other liquids used within the manufacturing process are tested regularly for concentration levels, pH, and are fully titrated regularly.
- Parts should be dry, clean and free from corrosion before packaging. Clean your product, preferably with a petroleum solvent or solvent emulsion cleaner. ARMOR VCI packaging will help *prevent* corrosion; however, it will not remove corrosion that has already occurred. To remove rust, ARMOR offers Metal Rescue® Rust Remover Bath.
- Package clean parts immediately after processing, manufacturing, or cleaning.
- Make sure that the ARMOR POLY VCI Bag is not ripped or torn to ensure that VCI vapors are contained inside the package
- Place part or multiple parts inside an ARMOR POLY VCI Bag and seal with a heat seal, for airtight storage.
- Store packaged parts in an area where the temperature and relative humidity are the most consistent possible. Do not store parts outside.
- While the parts are sitting in bins waiting to be repackaged or further processed, the VCI bag should be closed/folded over to protect parts from exposure to liquids, water, and moisture. A sheet of VCI paper can also be used by placing it on top, covering parts. Make sure that associates are using clean, dry gloves while packing parts.
- Pine, oak and corrugated are very acidic and can contribute greatly to corrosion issues. Avoid contact of metal with woods by placing ARMOR POLY between these materials.
- Provide frequent training to employees who are responsible for packaging or processing metal parts so that they understand how and why VCI is used in order for the employee to use these specialized products properly.

PROPERTIES

Gauge 0.004" +/- 10%.

For complete details, see ARMOR Technical Bulletin #143 & #144.

Products are nitrite-free; contain no secondary amines.

ARMOR POLY® products comply with directive 2002/95/EC (RoHS and RoHS2 2011/65/EU) of the European Parliament and do not contain Sulfur or halide compounds (fluorides, chlorides, bromides, or iodides).

Wash hands thoroughly after handling this product and before eating.

All products manufactured Armor Protective Packaging® are warranted to be first class products and free from defects in material and workmanship. Liability under this warranty is limited to the net purchase price of any of such products proven defective or at our option to the repair or replacement of said products upon their return to us transportation prepaid. All claims on defective products must be made in writing 30 days after the receipt of such products in your plant and prior to further processing or combining with other materials and products. We make no warranty, express or implied, as to the suitability of any of our products for any particular use, and we shall not be subject to liability from any damages resulting from their use in operations not under our direct control. This warranty is exclusive of all other warranties, express or implied, and no representative of ours or any other person is authorized to assume for us any other liability in connection with the sale of our products.

Revised 02/14/25