

RUST PREVENTION

CORROSION MANAGEMENT SOLUTIONS



ARMOR WRAP PAPER®

SILVER SHIELD®

FEATURES AND BENEFITS

SILVER SHIELD® is an anti-tarnish packaging designed for extended storage of noble metals. This neutral pH paper absorbs hydrogen sulfide vapors, which causes corrosion and tarnishing. Simply wrap or interleave your silver or silver-plated items in Silver Shield® paper and store for years of protection.

ARMOR WRAP® VCI (vapor corrosion inhibiting) papers are impregnated on BOTH sides, unlike most competitors' one-sided products. No guess work here! Two-sided protection is a benefit you'll receive only from ARMOR.

With service on 4 continents and in more than 25 countries, ARMOR is positioned to provide corrosion management solutions wherever and whenever you need them.



WHY ARMOR?

Armor Protective Packaging® provides the industry's cleanest, easiest, safest and most effective corrosion management systems for metal products to a global customer base. ARMOR's full line of vapor corrosion inhibitor (VCI) packaging products, desiccants and our rust removal and prevention liquids are designed to protect metals before, during and after transport or storage. ARMOR's industry reputation as a trusted business partner has been built by serving our customers and preserving their investments for more than a quarter-century.



APPLICATIONS

SILVER SHIELD® preserves the look and productivity of noble metals.

SILVER SHIELD® is an alternative to liquid dips and tarnish removers, and is ideal for long-term storage or export.

Additional applications include jewelry, coins, electrical components, musical instruments, circuit boards and computer accessories.

TECHNICAL DATA

ARMOR PROTECTIVE PACKAGING CORROSION MANAGEMENT SOLUTIONS

ARMOR WRAP® SILVER SHIELD®

Product Overview

A 35# neutral pH, bleached Kraft paper, impregnated with ARMOR® Tarnish and Corrosion Inhibitor formulation for noble metals. Silver Shield® is designed for contact tarnish inhibition and for storage of silver and other noble metals. Non-toxic.

Parameters

Finished Basis Weight: (24"X36"X500)	35 (+/-) 5%
Mullen Burst Test:	30 psi minimum
Elmendorf Tear Test:	
Machine Direction:	46 g/ply
Cross Machine Direction:	52 g/ply
Moisture %:	4.5 to 5.5% (+/-) 1%
Minimum Active Chemical Weight:	0.40 grams per sq. ft.

Recommended Applications

Noble metals including silver. Classified as twenty-four month minimum protection, when properly protected inside dry storage area in contact with paper.

Proper Storage

Material should be kept in original wrapping or the equivalent during storage of partial rolls or sheets (overnight, weekends, and holidays).

Armor Protective Packaging® recommends testing your product's compatibility with our ARMOR WRAP® SILVER SHIELD® paper.

CAUTION: Wash hands thoroughly after handling this product and before eating.

All products manufactured Armor Protective Packaging® are warranted to be first class products and free from defects in material and workmanship. Liability under this warranty is limited to the net purchase price of any of such products proven defective or at our option to the repair or replacement of said products upon their return to us transportation prepaid. All claims on defective products must be made in writing 30 days after the receipt of such products in your plant and prior to further processing or combining with other materials and products. We make no warranty, express or implied, as to the suitability of any of our product for any particular use, and we shall not be subject to liability from any damages resulting from their use in operations not under our direct control. This warranty is exclusive of all other warranties, express or implied, and no representative of ours or any other person is authorized to assume for us any other liability in connection with the sale of our products.

Published by: Armor Protective Packaging® Technical Services, Aug. 20, 2014

F: Product Standards/Product Data Sheets/Word files-DO NOT send to customers/ARMOR WRAP